

# ecom-B

The handiest glue gas analyser from ecom for inspections and short-term measurements on small combustion systems

Tested in accordance with  
EN 50379-2 and 1st BImSchV



## COMPACT FLUE GAS ANALYSIS

Made in Germany



### Reliable

Precise measurement results thanks to sensor calibration in the climate chamber



### Efficient

Switch on - measure - manage data - done!



ecom GmbH  
Am Großen Teich 2  
58640 Iserlohn  
info@ecom.de

**ecom**<sup>®</sup>  
Measurement Technology

„The better the setting, the higher the efficiency of the heating system“

# THE HANDIEST ECOM SOLUTION

## Checking and adjusting gas and oil heating systems



- Freehand measurement thanks to magnets on the back for attachment to metallic surfaces
- CO sensor overload protection with free purging without measurement interruption
- Long battery operation time with up to 150 measurements without charging thanks to integrated Li-Ion battery
- Up to 300 measurement data records storable

● = Basis EC ● = Optional EC



Technische Daten				✓ Standard	• Option
Measured values	Range	Resolution	Accuracy	* = Higher value prevails	
Maximum amount gas sensors					3
O <sub>2</sub>	0...21 %	0,1 vol. %	± 0,3 vol. %	✓	
CO (H <sub>2</sub> -comp.)	0...2.500 ppm (10.000 ppm)	1 ppm	± 20 ppm / 5 % of the measured value*	✓	
NO	0...5.000 ppm	1 ppm	± 5 ppm / 5 % of the measured value*		•
Other measured variables		Range	Resolution	Accuracy	
T-Gas	0...500 °C	0,1 °C	± 2 °C or 1,5 % of the measured value*		✓
T-Air	0...99 °C	0,1 °C	± 1 °C		✓
Pressure   ΔP	± 100 hPa	0,01 hPa	± 0,5 hPa or 1 % of the measured value*		✓

Technical data	
Calculation values	Range
CO <sub>2</sub>	0...CO <sub>2,max</sub>
Combustion efficiency (ETA)	0...120 %
Excess air (Lambda)	>1
Losses qA	0...100 %
Dew point	x° C
mg/m <sup>3</sup>	x mg/m <sup>3</sup>
mg/kWh	x mg/kWh
O <sub>2</sub> reference	x % O <sub>2</sub>

### Transport bag

Spacious textile bag for analyser and tools.



### ecom-P

Infrared thermal printer.



### CO-multi-hole probe

For measuring the CO concentration.



### Annular gap multi-hole probe

For measuring the O<sub>2</sub> concentration in the annular gap.



### Soot pump set

To determine the soot dot number.



### ecom-xRE

Readout head for digital burner controllers..



### ecom-UNO

Pocket-sized differential pressure gauge.



### e.CLOUD by ecom

Digital measurement data and customer management.

